


We Grow It



- ▲ Environmentally friendly; we are unique in our ability to grow and harvest our own trees from fully sustainable plantation forests
- ▲ FSC Certified (Full Chain of Custody). By buying products with the FSC label you are supporting the growth of responsible forest management worldwide.

We Make It



- ▲ Zero waste plant utilising our waste woodchip to generate steam which powers the plant
- ▲ Effective quality control systems
- ▲ Pressure treated for sapwood penetration
- ▲ Advanced exterior glue systems for fingerjointing and edge-gluing
- ▲ Kiln dried to 8-10% moisture content

We Protect It



- ▲ Preservative treated with environmentally advanced LOSP treatment
- ▲ No heavy metals used in treatment
- ▲ 20-Year Limited Warranty against rot and insects
- ▲ Guaranteed two coat primer system

You Build It



- ▲ Easy to install and use and maintain
- ▲ Exceptional strength and stability
- ▲ Defect free substrate

Product Sizes (Nominal)		
1 x 2		2 x 2
1 x 3		
1 x 4	5/4 x 4	2 x 4
1 x 6	5/4 x 6	2 x 6
1 x 8	5/4 x 8	2 x 8
1 x 10	5/4 x 10	2 x 10
1 x 12		2 x 12
All stock sizes available in 16' or 20' lengths.		
All above sizes are available in S1S2E		



Telephone: (503) 699-8685
 Fax: (503) 699-8827
sales@panpac-usa.com
www.panpac-usa.com



The mark of responsible forestry

SCS-COC-00218

© 1996 Forest Stewardship Council A.C.

© 2007 PanPac (USA) LLC. All rights reserved.

Contour Exterior™

TIMBER MOULDINGS & TRIMBOARD



The mark of responsible forestry
 SCS-COC-00218

© 1996 Forest Stewardship Council A.C.



PanPac (USA) LLC introduces a new range of sustainable timber mouldings and trimboard using the latest preservative treatment and finishing technologies. Contour Exterior mouldings and trimboards are protected from termites and fungal decay and are backed by a 20-Year Limited Warranty.

Protect your home with the sustainable and safe choice that is Contour Exterior.

Pan Pac (USA) LLC is an FSC (Chain of Custody) certified supplier.

Advanced technology and process controls are used throughout the manufacturing process to deliver a seamless, defect-free substrate, that will perform year after year under demanding conditions.

Installation

- ▲ Where Contour Exterior treated wood is cut or drilled, the freshly exposed areas must be coated with a suitable cut-end preservative product
- ▲ Contour Exterior treated wood products must be painted with a top coat within 30 days of installation
- ▲ Fill nail holes with exterior-grade wood filler and spot prime
- ▲ For best results, remove any dirt, dust, and touch sand before painting
- ▲ Paint with a premium-quality 100% acrylic latex house paint
- ▲ Not suitable for ground contact

Material Handling Information

Working with LOSP or Boron treated timber

- ▲ Wear gloves when working with the material
- ▲ If skin is exposed to the material wash exposed skin thoroughly after use
- ▲ Wear a dust mask and goggles when cutting or sanding the material
- ▲ Wash work clothes separately from other clothing
- ▲ Only use preserved wood that is visibly clean and free of surface residue
- ▲ Use fasteners, hardware, or any metal products as recommended by their manufacturer
- ▲ If wood is to be used in an interior application and becomes wet during construction, it should be allowed to dry before being covered or enclosed

Product Usage Guidelines

Preserved wood should not be used where it may come into direct or indirect contact with drinking water.

Do not use preserved wood for garden or plant mulch.

Do not use preserved wood in applications where it may come into contact with food, animal feed, or beehive enclosures.

Active-ingredient preservatives recognized for pressure treatment by the EPA (Environmental Protection Agency).

Wood is treated to conform to the AWPA Use Category 3A.

Protecting your Installation

Surfaces exposed by machining, drilling or cutting must be re-treated with a cut-end preservative and primed. Failure to re-treat will affect the value of the preservative.

Ripping, sawing, and planing are not recommended unless the wood is subsequently re-preserved to the original specification.

Adhesives and Sealants

Contour Exterior timber mouldings and trim products are compatible with most coatings, glues, and sealants and can normally be coated with most wood finishes.

Contour Exterior Mouldings and Trim products may be glued with resorcinol, phenol/resorcinol, urea formaldehyde glues, or polyurethane adhesives.

Contour exterior mouldings and trim are compatible with most sealants and mastics. Always follow the manufacturer's recommendations.

Storage

Contour Exterior wood products are treated with the LOSP or Boron preservative treatment systems and should be stored in a weatherproof warehouse in their original packaged form.

These appearance grade products should be treated with care on the construction site by keeping the material covered and off the ground.

Disposal & Cleanup Recommendations

Preserved wood may be disposed of in landfills or burned in commercial or industrial incinerators or boilers in accordance with federal, state, and local regulations.

All sawdust and construction debris should be cleaned up and disposed of after construction safely in a municipal landfill in accordance with federal, state and local regulations.

Active Ingredients in our LOSP Treatment

Tebuconazole: A fungicide used on grapes, grains & fruit.

Propiconazole: A fungicide used on cereals, coffee, peanuts, corn & stone fruits.

Permethrin: An insecticide used to provide insect control for stored fruits and grains.